

离合器型号 Clutch Designation			轴径	外形尺寸 Boundary Dimensions			传动力矩	极限转速 Limiting Speed		重量 Mass
现行的 Current	国外厂商 Otherfactory		shaft Diameter	Fw	D	C	Torque Ma	n	nA	近似 Approx
	INA	Torrington	mm	mm			N	rpm		g
H F0406	H F0406	FC -4	4	4	8	6	0.34	34000	14000	1
H F0612	H F0612	FC S -6	6	6	10	12	1.76	23000	13000	3
H F0812	H F0812	-	8	8	12	12	3.15	17000	12000	3.5
H F1012	H F1012	FC L-10K	10	10	14	12	5.3	14000	11000	4
H F1216	H F1216	FC -12	12	12	18	16	12.2	11000	8000	11.6
H F1416	H F1416	-	14	4	20	16	17.3	9500	8000	13
H F1616	H F1616	FC -16	16	6	22	16	20.5	8500	7500	14
H F1816	H F1816	-	18	18	24	16	24.1	7500	7500	15.5
H F2016	H F2016	FC -20	20	20	26	16	28.5	7000	6500	17
H F2520	H F2520	FC -25	25	25	32	20	66	5500	6500	30.9
H F3020	H F3020	FC -30	30	30	37	20	90	4500	4500	36
H F3520	H F3520	FC S -35	35	35	42	20	121	3900	3900	40
H F0822	H F0822	FC B L-B K	8	8	12	22	3.15	17000	12000	6.3
H F1022	H F1022	-	10	10	14	22	5.3	14000	11000	7.4
H F1226	H F1226	FC B -12	12	12	18	26	12.2	11000	8000	18
H F1426	H F1426	-	14	14	20	26	17.3	9500	8000	20.3
H F1626	H F1626	FC B -16	16	16	22	26	20.5	8500	7500	22
H F1826	H F1826	-	18	18	24	26	24.1	7500	7500	24.4
H F2026	H F2026	FC B -20	20	20	26	26	28.5	7000	6500	27
H F2530	H F2530	FC B -25	25	25	32	30	66	5500	5500	44
H F3030	H F3030	FC B -30	30	30	37	30	90	4500	4500	51
H F3530	H F3530	-	35	35	42	30	121	3900	3900	58