

穿孔型 Open end		重量 Mass	封口型 Closed end		重量 Mass	shaft Diameter	Boundary Dimensions mm 外形尺寸			基本额定负荷 N Basic Load Rating		极限转速 Limiting Speed rpm
现行的 Current	被取代的 Substituted	g	现行的 Current	被取代的 Substituted	g	mm	Fw	D	C	动C r Dynamic	静C or Static	润滑油 Oil
F-0608	30941/6	2.5	-	-	-	6	6	10	8	3 080	5 800	12 000
F-0810	50941/8	3.7	-	-	-	6	8	12	10	4 050	7 150	13 000
FH -0810	941/8	7	-	-	-	8	8	14	10	5 200	7 150	7 400
FH -0812	942/8	9	-	-	-	8	8	14	12	4 550	7 150	7 400
F-0910	50941/9	4	-	-	-	8	9	13	10	4 900	8 050	12 000
FH -0910	941/9	6	-	-	-	9	9	15	10	8 000	11 500	7 100
FH 9×15×13	942/9	8	-	-	-	9	9	15	13	8 560	12 800	7 100
F-1010	50941/10	4.2	-	-	-	9	10	14	10	5 700	9 350	11 000
FH -1010	941/9	6.5	-	-	-	10	10	16	10	6 350	10 800	11 000
F-10×16×15	942/10	12	-	-	-	10	10	16	15	6 890	11 500	7 100
F-1212	60941/12	6	-	-	-	10	12	16	12	6 380	10 900	7 100
F12×17×12	941/12	8	-	-	-	10	12	17	12	8 400	11 900	7 100
F12×17×15	942/12	10.5	-	-	-	12	12	17	15	9 000	12 500	7 100
F12×17×18	943/12	13	-	-	-	12	12	17	18	9 800	13 500	7 100
F15×20×12	941/15	10	-	-	-	12	15	20	12	8 400	11 900	7 100
F15×20×16	942/15	13.6	-	-	-	12	15	20	16	9 500	12 800	7 100
F15×20×20	943/15	17.2	-	-	-	15	15	20	20	10 500	16 000	7 100
FY 15×20×20	Y /152020	20	-	-	-	15	15	20	20	10 500	16 000	7 100
F-1512	30941/15	12	-	-	-	15	15	21	12	9 700	15 900	8 100
F-1616	50941/16	17	-	-	-	16	16	22	16	14 100	25 900	7 700
F-1712	30941/17	13	-	-	-	16	17	23	12	10 600	21 600	7 300
F-1714	941/17	15	-	-	-	17	17	23	14	12 500	22 500	7 300
F-1718	942/17	21	-	-	-	17	17	23	18	13 800	24 800	7 300
F-1816	50941/18	18	-	-	-	18	18	24	16	15 000	29 100	6 900
F-2014	941/20	17	-	-	-	18	20	26	14	15 800	40 500	6 900
F-2020	942/20	26	-	-	-	20	20	26	20	18 800	42 500	6 900
F20×26×25	943/20	33	-	-	-	20	20	26	25	20 500	35 500	6 300
F-2516	941/25	28	-	-	-	20	25	32	16	18 700	37 900	5 100
F-2522	942/25	40	-	-	-	20	25	32	22	11 000	16 500	5 100
F25×32×25	943/25	43	-	-	-	25	25	32	25	11 500	18 500	5 100
F25×33×08	Y /253308	16.7	-	-	-	25	25	33	8	12 200	16 800	4 300
F-2820	60941/28	118	-	-	-	28	28	35	20	25 700	58 300	4 600
F-3020	60941/30	42	M F -3020	65941/30	48	28	30	37	20	26 800	62 500	4 300
F30×38×16	941/30	37.5	-	-	-	28	30	38	16	25 500	57 500	4 600
F30×38×24	942/30	37.5	-	-	-	30	30	38	24	28 800	64 500	4 300
F30×38×32	943/30	81.5	-	-	-	30	30	38	32	34 500	78 900	4 300
F-3216	40941/32	35	-	-	-	32	32	39	16	25 800	61 500	4 300
F-3520	60941/35	49	-	-	-	32	35	42	20	24 000	69 100	3700
F35×43×16	941/35	41	-	-	-	35	35	43	16	23 500	68 000	3700
F35×43×25	942/35	72	-	-	-	35	35	43	25	38 700	86 200	3200
F35×43×32	943/35	90	-	-	-	35	35	43	32	40 500	97 800	3200
F-4020	60941/40	56	-	-	-	35	40	47	20	30 300	82 600	3300

FH -4032	942/40	88	M F H -4032	86942/40	95	40	40	50	32	42 500	108 000	2600
FH 40x50x38	943/40	105	-	-	-	40	40	50	38	44 800	118 500	2600
F-4520	-	62	-	-	-	45	45	52	20	30 400	90 100	2900
FH 45x55x38	943/45	140	-	-	-	45	45	55	38	45 800	128 000	2900
F-5020	50941/50	78	-	-	-	50	50	58	20	35 800	98 000	2600
FH 50x60x38	943/50	145	-	-	-	50	50	60	38	50 500	145 800	2600
F60x68x40	943/60	185	-	-	-	60	60	68	40	50 200	145 000	2600