

轴承型号 Bearing Designation		轴径	外形尺寸 Boundary Dimensions			基本额定负荷 Basic Load Rating		极限转速 Limiting Speed	重量 Mass 近似 Approx
现行的 Current	被取代的 Substituted	Shaft Diameter	Fw	D	C	动Cr Dynamic	静Cor Static	油润滑 Oil	g
		mm	mm			N		rpm	
无内圈									
RNAV 4002	4084102	21.87	21.87	32	17	10 800	29 800	4500	45
RNAV 4003	4084103	24.3	24.3	35	18	17 900	37 900	4300	62
RNAV 4004	4084104	28.7	28.7	42	22	28 150	60 900	3900	114
RNAV 4005	4084105	33.5	33.5	47	22	33 800	70 800	3700	129
RNAV 4006	4084106	40.1	40.1	55	25	49 900	96 500	3500	193
RNAV 4007	4084107	45.9	45.9	62	27	47 600	122 800	3100	259
RNAV 4008	4084108	51.6	51.6	68	28	49 900	137 900	2700	304
RNAV 4009	4084109	57.4	57.4	75	30	52 500	153 500	2600	390
RNAV 4010	4084110	62.1	62.1	80	30	55 700	166 000	2500	426
RNAV 4011	4084111	69.8	69.8	90	35	68 500	225 800	2300	645
RNAV 4012	4084112	74.6	74.6	95	35	75 400	239 000	2100	677
RNAV 4013	4084113	80.3	80.3	100	35	79 500	256 900	1900	692
RNAV 4014	4084114	88	88	110	40	98 800	354 900	1700	950
RNAV 4015	4084115	92.7	92.7	115	45	101 800	372 900	1600	1 000
RNAV 4016	4084116	100.3	100.3	125	45	102 900	373 900	1500	1 400
RNAV 4017	4084117	104.8	104.8	130	45	103 800	374 800	1400	1 540
有内圈									
RAV 4002	4084102	15	15	32	17	10 800	29 800	4500	76
RAV 4003	4084103	17	17	35	18	17 900	37 900	4300	94
RAV 4004	4084104	20	10	42	22	28 150	60 900	3900	170
RAV 4005	4084105	25	25	47	22	33 800	70 800	3700	195
RAV 4006	4084106	30	30	55	25	49 900	96 500	3500	299
RAV 4007	4084107	35	35	62	27	47 600	122 800	3100	402
RAV 4008	4084108	40	40	68	28	49 900	137 900	2700	482
RAV 4009	4084109	45	45	75	30	52 500	153 500	2600	617
RAV 4010	4084110	50	50	80	30	55 700	166 000	2500	669
RAV 4011	4084111	55	55	90	35	68 500	225 800	2300	1 030
RAV 34012	4084112	60	60	95	35	75 400	239 000	2100	1 081
RAV 4013	4084113	65	64	100	35	79 500	256 900	1900	1 156
RAV 4014	4084114	70	70	110	40	98 800	354 900	1700	1 666
RAV 4015	4084115	75	75	115	45	101 800	372 900	1600	1 762
RAV 4016	4084116	80	80	125	45	102 900	373 900	1500	2 450
RAV 4017	4084117	85	85	130	45	103 800	374 800	1400	2 500